

# Specifications

Model			SCC-C6433(P)	SCC-C6435(P)
Camera Type			Color	
Image	Device		1/4" Super HAD CCD	1/4" Ex-View HAD CCD
	Effective Pixels	NTSC	768(H) x 494(V)	768(H) x 494(V)
		PAL	752(H) x 582(V)	752(H) x 582(V)
Minimum Scene Illumination		Color	0.6 Lux(15IRE, Sens-up Off)	0.3 Lux(15IRE, Sens-up Off)
			0.002 Lux(15IRE, Sens-up 256x)	0.001 Lux(15IRE, Sens-up 256x)
		B/W	0.06 Lux(15IRE, Sens-up Off)	0.03 Lux(15IRE, Sens-up Off)
			0.0002 Lux(15IRE, Sens-up 256x)	0.0001 Lux(15IRE, Sens-up 256x)
PAN/TILT	Speed	Manual Pan	0.1~180°/sec	
		Preset Pan	400°/sec	
		Manual Tilt	0.1~90°/sec	
		Preset Tilt	200°/sec	
	Range	Panning	0~360° (Endless)	
		Tilting	0~180°	
	Number of Auto PAN		4	
	Number of Preset		128	
	Number of Pattern		3	
	Functions	Number of Privacy Zone		16
Day & Night		Color/BW/Auto (Moving Filter)		
Line Lock		INT/Line Lock		
White Balance		ATW1/ATW2/AWC/MANUAL		
D-Zoom		Yes (~16x)		
High Speed Shutter		Yes (OFF ~ 1/10K)		
Motion Detection		Yes		
Sens Up		Yes (2x ~ 256x)		
Camera ID		Max 20 Character		
Remote Control		RS485(Half&Full Duplex)/RS422		
Alarm		Input	8	
		Output	3(Open Collector 1 relay)	
Wide Dynamic Range		N/A	Yes	
Horizontal Resolution			540(Color)/570(BW) TV Lines	
Video Output			VBS 1.0Vp-p	
S/N Ratio			About 50 dB	
Lens	Focal Length		3.55 ~ 113mm	
	Zoom Ratio		32x Optical	
	Aperture Ratio		F1.69(W)/F4.17(T)	
	Viewing Angle	Tele	1.78°(H) x 1.34°(V)	
		Wide	56.41°(H) x 43.01°(V)	
Operating Temperature			-10°C ~ + 50°C	
Operating Humidity			Less than 90%	
Power Requirement			NTSC : AC24 V, 60Hz / PAL : AC24 V, 50Hz	
Power Consumption			19W	20W
LED Indicator			Yes	
Dimensions			177(φ) X 233.5(H)mm	
Weight			2400g	
Color			Silver	